

English GO/NOGO Gage Assemblies

Use these GO/NOGO assemblies for in-process inspection on the shop floor. Detect out of tolerances before your customer does. Available in English Class Z, Class X and Class XX.



ENGLISH GO/NOGO GAGES

Diameter Range	Class Z GO/NOGO Assembly	Class Z GO <i>or</i> NOGO Assembly	Class X GO/NOGO Assembly	Class X GO <i>or</i> NOGO Assembly	Class XX GO/NOGO Assembly	Class XX GO Assembly <i>or</i> NOGO Assembly
.011" - .0755"	\$13.57	\$ 8.95	\$35.52	\$19.64	\$ 71.04	\$39.27
.076" - .1805"	13.45	8.66	30.90	17.33	61.80	34.65
.181" - .2815"	14.44	9.53	31.19	17.61	62.37	35.22
.282" - .4065"	14.73	9.82	32.05	18.19	64.11	36.39
.407" - .5005"	17.04	11.84	34.36	19.64	68.73	39.27
.501" - .5105"	18.48	12.13	43.60	24.26	87.21	48.51
.511" - .6255"	22.52	15.02	47.64	27.72	95.28	55.44
.626" - .6355"	25.58	16.75	47.64	27.72	95.28	55.44
.636" - .7505"	27.03	17.90	49.09	28.88	98.19	57.75
.751" - .7605"	31.65	20.21	56.60	32.63	113.19	65.25
.761" - .8325"	38.69	25.99	62.89	37.83	125.77	75.66
.833" - .9165"	39.85	27.14	62.89	37.83	125.77	75.66
.917" - 1.0005"	40.71	28.30	62.89	37.83	125.77	75.66

One complete GO/NOGO gage includes: one Plus member (GO), one Minus member (NOGO), one Double End Handle with Bushings assembled.

GO gage includes: one Plus member with Single End Handle and Bushing assembled.

NOGO gage includes: one Minus member with Single End Handle and Bushing assembled.

GO/NOGO gages are available with special diameter or length gages, prices on request.

Gage Handles marked with size and direction of tolerance. *Additional markings \$0.15 per character.