



Custom Progressive Gages*

When you need to check parts quickly, Progressive plug gages are the best choice. Both the GO and NOGO diameters are stepped on a single gage member. All members are securely attached to either a Trilock or Taperlock handle. All handles are marked with sizes and direction of tolerance.

- Class XX, X, Y, or Z
- NIST traceable
- GO, NOGO tolerances
- Tool Steel 60/62 Rockwell C
- Certificate of Accuracy included
- Additional marking available \$0.50 per character

Unilateral Tolerance, GO - Plus Tolerance, NOGO - Minus Tolerance; Chrome Plates: Add 30%
 * -Not returnable for credit or cancellation

Size-Range	Class	Tolerance Inches	Member Length	GO Portion	NOGO Portion	Quantities			Handle	
						1	2-4	5-10	No.	Price
TAPERLOCK STYLE	XX	.00002				\$ 110.23	\$ 102.24	\$ 97.43		
.105 in. to .150 in. 2.67 mm to 3.81 mm	X	.00004	23/32 in.	3/8 in.	7/32 in.	89.46	84.67	79.88	00	\$ 14.62
	Y	.00007	18.3mm	9.5mm	5.6mm	76.68	70.29	67.10		
	Z	.00010				63.90	60.71	57.51		
.1501 in. to .230 in. 3.81 mm to 5.84 mm	XX	.00002				100.64	95.85	91.06		
	X	.00004	13/16 in.	13/32 in.	9/32 in.	84.67	79.88	76.68	0	14.62
	Y	.00007	20.6mm	10.3mm	7.1mm	75.08	68.69	65.50		
	Z	.00010				57.51	54.32	51.12		
.2301 in. to .365 in. 5.84 mm to 9.27 mm	XX	.00002				108.63	100.64	95.85		
	X	.00004	13/16 in.	3/4 in.	5/16 in.	87.86	83.07	78.28	1	14.62
	Y	.00007	30.2mm	19.1mm	7.9mm	76.68	70.29	67.10		
	Z	.00010				60.71	57.51	54.32		
.3651 in. to .510 in. 9.27 mm to 12.95 mm	XX	.00002				115.02	108.63	102.24		
	X	.00004	11/2 in.	1 in.	3/8 in.	92.66	87.86	83.07	2	14.62
	Y	.00007	38.1mm	25.4mm	9.5mm	81.47	76.68	73.49		
	Z	.00010				63.90	60.71	57.49		
.5101 in. to .825 in. 12.95 mm to 20.96 mm	XX	.00002				119.80	113.41	107.03		
	X	.00004	17/8 in.	11/4 in.	1/2 in.	95.85	91.06	86.27	3	14.62
	Y	.00007	47.6mm	31.8mm	12.7mm	86.27	81.47	76.68		
	Z	.00010				67.10	63.90	60.71		
.8251 in. to 1.135 in. 20.96 mm to 28.83 mm	XX	.00003				140.57	132.58	126.19		
	X	.00006	21/8 in.	13/8 in.	5/8 in.	108.63	100.64	95.85	4	14.62
	Y	.00009	54.0mm	34.9mm	15.9mm	89.46	84.67	79.88		
	Z	.00012				78.28	73.49	68.69		
1.1351 in. to 1.510 in. 28.83 mm to 38.35 mm	XX	.00003				151.75	143.78	135.79		
	X	.00006	23/8 in.	11/2 in.	3/4 in.	135.79	127.80	115.62	5	16.45
	Y	.00009	60.3mm	38.1mm	19.1mm	108.63	100.64	95.85		
	Z	.00012				91.06	86.27	81.47		
TRILOCK STYLE	XX	.00004				225.24	214.06	201.28		
1.5101 in. to 2.010 in. 38.35 mm to 51.05 mm	X	.00008	27/8 in.	17/8 in.	7/8 in.	180.51	169.34	161.34	5 1/2	20.19
	Y	.00012	73.0mm	47.6mm	22.2mm	158.16	150.17	142.18		
	Z	.00016				127.80	121.41	115.02		
2.0101 in. to 2.510 in. 51.05 mm to 63.75 mm	XX	.00004				282.75	266.77	254.00		
	X	.00008	3 in.	2 in.	7/8 in.	228.43	217.25	204.47	6	20.94
	Y	.00012	76.2mm	50.8mm	22.2mm	193.29	183.70	174.12		
	Z	.00016				159.74	151.75	143.78		
2.5101 in. to 3.010 in. 63.75 mm to 76.45 mm	XX	.00005				307.32	305.11	289.14		
	X	.00010	3 in.	2 in.	7/8 in.	263.58	250.80	236.42	7	22.57
	Y	.00015	76.2mm	50.8mm	22.2mm	226.84	215.65	202.87		
	Z	.00020				186.90	177.31	166.13		
3.0101 in. to 3.510 in. 76.45 mm to 89.15 mm	XX	.00005				381.78	361.03	339.48		
	X	.00010	3 in.	2 in.	7/8 in.	293.93	279.55	263.58	7	22.57
	Y	.00015	76.2mm	50.8mm	22.2mm	261.98	249.20	234.82		
	Z	.00020				218.85	207.67	196.48		
3.5101 in. to 4.010 in. 89.15 mm to 101.85 mm	XX	.00005				444.09	400.12	397.77		
	X	.00010	31/8 in.	21/8 in.	7/8 in.	359.43	341.86	322.69	7	22.57
	Y	.00015	79.4mm	54.0mm	22.2mm	308.31	290.74	276.36		
	Z	.00020				258.79	246.01	231.63		
4.0101 in. to 4.510 in. 101.85 mm to 114.55 mm	XX	.00005				503.19	479.23	453.67		
	X	.00010	31/8 in.	21/8 in.	7/8 in.	404.16	383.39	362.62	7	22.57
	Y	.00015	79.4mm	54.0mm	22.2mm	351.44	316.45	286.89		
	Z	.00020				289.14	274.76	258.79		

