



# Custom Progressive Gages\*

When you need to check parts quickly, Progressive plug gages are the best choice. Both the GO and NOGO diameters are stepped on a single gage member. All members are securely attached to either a Trilock or Taperlock handle. All handles are marked with sizes and direction of tolerance.

- Class XX, X, Y, or Z
- NIST traceable
- GO, NOGO tolerances
- Tool Steel 58/60 Rockwell C
- Certificate of Accuracy included
- Additional marking available \$0.50 per character

**Unilateral Tolerance, GO - Plus Tolerance, NOGO - Minus Tolerance; Chrome Plates: Add 100%**  
 \* -Not returnable for credit or cancellation

AGD Progressive Member						Handle	
Size-Range	Class	Tolerance Inches	Member Length	GO Portion	NOGO Portion	No.	Price
<b>TAPERLOCK STYLE</b>							
.105 in. to .150 in. 2.67 mm to 3.81 mm	XX	.00002					\$141.53
	X	.00004	23/32 in.	3/8 in.	7/32 in.	00	\$ 18.24
	Y	.00007	18.3 mm	9.5 mm	5.6 mm		98.45
	Z	.00010					82.05
.1501 in. to .230 in. 3.81 mm to 5.84 mm	XX	.00002					129.21
	X	.00004	13/16 in.	13/32 in.	9/32 in.	0	18.24
	Y	.00007	20.6 mm	10.3 mm	7.1 mm		96.40
	Z	.00010					73.84
.2301 in. to .365 in. 5.84 mm to 9.27 mm	XX	.00002					139.47
	X	.00004	13/16 in.	3/4 in.	5/16 in.	1	18.24
	Y	.00007	30.2 mm	19.1 mm	7.9 mm		98.45
	Z	.00010					77.95
.3651 in. to .510 in. 9.27 mm to 12.95 mm	XX	.00002					147.68
	X	.00004	1-1/2 in.	1 in.	3/8 in.	2	18.24
	Y	.00007	38.1 mm	25.4 mm	9.5 mm		104.60
	Z	.00010					82.05
.5101 in. to .825 in. 12.95 mm to 20.96 mm	XX	.00002					153.83
	X	.00004	1-7/8 in.	1-1/4 in.	1/2 in.	3	18.24
	Y	.00007	47.6 mm	31.8 mm	12.7 mm		110.77
	Z	.00010					86.16
.8251 in. to 1.135 in. 20.96 mm to 28.83 mm	XX	.00003					180.50
	X	.00006	2-1/8 in.	1-3/8 in.	5/8 in.	4	18.24
	Y	.00009	54.0 mm	34.9 mm	15.9 mm		114.86
	Z	.00012					100.51
1.1351 in. to 1.510 in. 28.83 mm to 38.35 mm	XX	.00003					194.85
	X	.00006	2-3/8 in.	1-1/2 in.	3/4 in.	5	20.53
	Y	.00009	60.3 mm	38.1 mm	19.1 mm		139.47
	Z	.00012					116.92
<b>TRILOCK STYLE</b>							
1.5101 in. to 2.010 in. 38.35 mm to 51.05 mm	XX	.00004					289.21
	X	.00008	2-7/8 in.	1-7/8 in.	7/8 in.	5-1/2	25.19
	Y	.00012	73.0 mm	47.6 mm	22.2 mm		203.08
	Z	.00016					164.08
2.0101 in. to 2.510 in. 51.05 mm to 63.75 mm	XX	.00004					363.05
	X	.00008	3 in.	2 in.	7/8 in.	6	26.14
	Y	.00012	76.2 mm	50.8 mm	22.2 mm		248.19
	Z	.00016					205.11
2.5101 in. to 3.010 in. 63.75 mm to 76.45 mm	XX	.00005					394.59
	X	.00010	3 in.	2 in.	7/8 in.	7	28.16
	Y	.00015	76.2 mm	50.8 mm	22.2 mm		291.26
	Z	.00020					239.98
3.0101 in. to 3.510 in. 76.45 mm to 89.15 mm	XX	.00005					490.21
	X	.00010	3 in.	2 in.	7/8 in.	7	28.16
	Y	.00015	76.2 mm	50.8 mm	22.2 mm		336.39
	Z	.00020					281.00
3.5101 in. to 4.010 in. 89.15 mm to 101.85 mm	XX	.00005					593.98
	X	.00010	3-1/8 in.	2-1/8 in.	7/8 in.	7	29.34
	Y	.00015	79.4 mm	54.0 mm	22.2 mm		412.37
	Z	.00020					346.13
4.0101 in. to 4.510 in. 101.85 mm to 114.55 mm	XX	.00005					673.02
	X	.00010	3-1/8 in.	2-1/8 in.	7/8 in.	7	29.34
	Y	.00015	79.4 mm	54.0 mm	22.2 mm		470.05
	Z	.00020					386.72

